

**mazda****MAZDA BT-50 SPECIFICATION**

DIMENSION & WEIGHT		Double 4x4 2.5L	Double Cab 4x4 3.0L
Overall Length	mm	5169	5169
Overall Width	mm	1807	1807
Overall Height	mm	1762	1762
Wheelbase	mm	3000	3000
Min. Ground Clearance	mm	207	207
Cargo-box Length	mm	1530	1530
Cargo-box Width	mm	1456	1456
Cargo-box Height	mm	465	465
ENGINE			
Type		MZ-DE 2.5L Diesel, 4-Cyl. 12-Valve, SOHC, Indirect Injection Turbo with Intercooler	MZR-CD 3.0L Diesel, 4-Cyl. 16-Valve, DOHC, Direct Injection Turbo with Intercooler
Charging System		Turbocharger	Turbocharger
Displacement	cc	2499	2953
Bore x Stroke	(mm x mm)	93 x 92	96 x 102
Fuel Supply System		Mechanical Fuel Injection	Electronic Fuel Injection
Fuel Tank Capacity	L	70	70
PERFORMANCE			
Maximum Power	HP (kW)/rpm	107 (80) /3500	156 (115) /3200
Maximum Torque	Nm / rpm	257/2000	380/1800
CHASSIS & SUSPENSION			
Steering Type		Ball & Nut	Ball & Nut
Transmission Type		Manual Transmission	Manual Transmission
Power-assisted steering system		Engine-rpm sensing	Engine-rpm sensing
Brake Type	Front	Ventilated Disc	Ventilated Disc
	Rear	Drum (leading/trailing with auto adjuster)	Drum (leading/trailing with auto adjuster)
Suspension Type	Front	Independent, double wishbone with torsion bar springs	Independent, double wishbone with torsion bar springs
	Rear	Rigid leaf spring	Rigid leaf spring
Tyres & Wheels		245/70R16, Alloy 16"	245/70R16, Alloy 16"
SAFETY FEATURES			
Retractable Key		v	v
Power Door Locks		v	v
Burglar Alarm		v	v
Keyless Entry		v	v
Immobilizer		v	v